

ZR24K3E-PFJ



HFC, R-407C, Dew Point, 50 Hz, 1 - Phase, 220/240 V
Air Conditioning

Production Status: Non U.S. model with restricted sales - Contact your Emerson Climate Technologies Representative.

Performance

Evap(°F)/Cond(°F)	45/130	45/100
RG(°F)/Liq(°F)	65/115	65/85
Capacity (Btu/hr):	19400	23600
Power (Watts):	1940	1310
Current (Amps):	9.2	6.2
EER (Btu/Wh):	10.0	18.1
Mass Flow (lbs/hr):	282.0	293.0
Sound Power(dBA):	65 Ave	70 Max
Vibration (mils(peak-peak)):	2.0 Ave	3.0 Max
Record Date:	2005-04-15	

Mechanical

Number of Cylinders:	0	Displ (in ³ /Rev):	2.076
Bore Size (in):	0.0	Displ (ft ³ /hr):	209.0407
Stroke (in):	0.0		
Overall Length (in):	9.567	Mounting Length (in):	7.5
Overall Width (in):	9.567	Mounting Width(in):	7.5
Overall Height (in):	14.84	Mounting Height (in):	15.076*
Suction Size (in):	3/4 Stub		
Discharge Size (in):	1/2 Stub		
Initial Oil Charge (oz):	38		
Oil Recharge (oz):	34		
Net Weight (lbs):	55.0		
Internal Free Volume (in ³):	175.0		
HorsePower	2.0		
* Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	58.0	MCC (Amps):	16.0	UL File No.:	
LRA-Half Winding:		RPM:	2900	UL File Date:	14-Jun-1994
LRA-Low*:	53.0	Max Operating Current:	13.1	CSA File No.:	
RLA(=MCC/1.4; use for contactor selection):	11.4				
RLA (=MCC/1.56; use for breaker & wire size selection):	10.3				
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

Alternate Applications

Refrigerant	Frequency(Hz)	Phase	Voltage	Application
R-407C HFC	60	1	265	Air Conditioning